	PARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER				
TRANSMITTAL LETTER	TO THE UNITED STATES	0696-0178P				
DESIGNATED/ELECTED OFFICE (DO/EO/US)		U.S. APPLICATION NO. (If known, see 37 CFR 1.5)				
CONCERNING A FILING	09 MB 30869					
INTE NATIONAL APPLICATION NO.	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED				
PCT/FI99/00910	November 1, 1999	November 2, 1998				
TITLE OF INVENTION COATED PAPERBOARD, PROCESS	FOR MANUFACTURING THE SAME AND	PRODUCTS OBTAINED THEREOF				
APPLICANT(S) FOR DO/EO/US AHO, Yrjo; PENT	TINEN, Tapani; SALMINEN, Risto;	FOSTER, Bruce				
Applicant herewith submits to the United States						
3. This express request to begin national	omission of items concerning a filing under 35 U.S. examination procedures (35 U.S.C. 371(f)) at a	any time rather than delay				
	applicable time limit set in 35 U.S.C. 371(b) a	and PCT Articles 22 and 39 (1).				
5. A copy of the International Application	months from the priority date (Article 31).					
		Duranu) WO 00/26025				
a. is transmitted herewith (require b. has been transmitted by the International contents of the contents	ed only if not transmitted by the International E	Sureau). WO 00/20023				
	on was filed in the United States Receiving Of	Fice (PO/LIS)				
	the International Application as filed (35 U.S.C.					
a. is transmitted herewith.	ie international Application as fried (55 U.S.C	371(6)(2)).				
	under 25 II S.C. 154(d)(4)					
b. has been previously submitted under 35 U.S.C. 154(d)(4)						
7. Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).						
 a. are transmitted herewith (required only if not transmitted by the International Bureau). b. have been transmitted by the International Bureau. 						
<u> </u>	the time limit for making such amendments ha	os NOT avnirad				
d. have not been made and will no		is NOT expired.				
	e amendments to the claims under PCT Article	e 10 (35 II S C - 371(c)(3))				
9. An oath or declaration of the inventor		c 19 (33 0.s.c. 3/1(c)(3)).				
	e annexes of the International Preliminary Exa	umination Report under PCT Article 36				
(35 U.S.C. 371(c)(5)).	e aimexes of the international Freimmary Exa	animation Report under FC1 Article 30				
Mems 11. to 20. below concern document(s)	or information included:	•				
K-7		·				
	under 37 CFR 1.97 and 1.98-International Sec	• '				
12. An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.						
13. A FIRST preliminary amendment.						
14. A SECOND or SUBSEQUENT preliminary amendment.						
15. A substitute specification.						
16. A change of power of attorney and/or address letter.						
	uence listing in accordance with PCT Rule 13t	Į				
	national application under 35 U.S.C. 154(d)(4)	1				
	ge translation of the international application u	nder 35 U.S.C. 154(d)(4).				
20. Other items or information:	atamatica I Parliada a P	(DOT(DE A (400) and A (
1.) PC1 Substitute Claims Letter w/ I2.) PCT Request3.) One (1) sheet of Formal Drawings	nternational Preliminary Examination Report (PC1/IPEA/409) and claims				
	•					

JC18 Rec'd PCT/PTO 0 2 MAY 2001

U.S. APPLICATION NO (if known, see 37	U.S. APPLICATION NO (if known, see 37 CFR 1.5) INTERNATIONAL APPLICATION NO				ATTORNEY'S DOCKET NUMBER		
. 09 / E	8308 69	70069 PCT/F199/00910				0696-0178P	
21. The following fees	, , , , , , , , , , , , , , , , , , , 				CAI	CULATIONS	PTO USE ONLY
BASIC NATIONAL F		(1)-(5):					
	reliminary examination						
	h fee (37 CFR 1.445(a)			61 000 00			
and regernational Sear	ch Report not prepared	by the	EPO or JPO	\$1,000.00			
International prelimina	ry examination fee (37	CFR 1.	482) not paid to				
			he EPO or JPO	\$860.00			
			482) not paid to USPTO	0710.00			
but international search	1 1ee (37 CFR 1.443(a)	(2)) paic	l to USPTO	\$710.00			
International prelimina	ry examination fee (37	CFR 1.	482) paid to USPTO				
			e 33(1)-(4)	\$690.00			
	ry examination fee (37			#100.00		W	
			1)-(4) FEE AMOUNT =	\$100.00	\$	1000.00	
Surcharge of \$130.00 fo				⊠ 30	\$	130.00	
months from the earlies	NUMBER FILE		NUMBER EXTRA	DATE			
Total Claims	24 - 20 =		4	RATE X \$18.00	<u>-</u>	72.00	
Independent Claims			0	X \$80.00	\$	72.00	
•		1:1-1-1			\$. 0	
MULTIPLE DEPENDI			Yes	+ \$270.00	\$	270.00	
			F ABOVE CALCULA		\$	1472.00	
Applicant claims sr	nall entity status. See 3	7 CFR	.27. The fees indicated ab	ove are	\$	0	
reduced by 1/2.					\$	1472.00	
Processing fee of \$130.00 for furnishing the English translation later than 20 30					. D	14/2.00	
months from the earliest claimed priority date (37 CFR 1.492(f)).					\$	0	
, TOTAL NATIONAL FEE =				\$	1472.00		
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be							
			.28, 3.31). \$40.00 per pro		\$	0	
			TOTAL FEES ENC	LOSED =	\$	1472.00	
						Amount to be:	\$
						refunded	
						charged	\$
a. A check in the an	nount of \$ 1472.00 to	cover th	e above fees is enclosed.				
b. Please charge my	Deposit Account No.		in the amount of \$	to as	41.	a abassa Casa	
	of this sheet is enclose		in the amount of 5	10 CC	over in	e above fees.	
							,
	er is hereby authorized Deposit Account No. 0		ge any additional fees which	ch may be req	uired,	or credit any	
overpayment to i	Deposit Account No. 0	2-2448 .					
NOTE: Where an a	ppropriate time limit	under 3	87 CFR 1.494 or 1.495 ha	s not been m	et, a p	etition to reviv	e (37 CFR
1.137(a) or (b)) mus	t be filed and granted	to resto	re the application to pen	ding status.			
Send all correspondence to:							
Birch, Stewart, Kolasch & Birch, LLP or Customer No. 2292							
P.O. Box 747 Falls Church, VA 22040-0747							
(703)205-8000	40 T U T U T I			An		1	0
•				////	1,	My	
Date: May 2, 2001			I	Ву	رمر	- the	
	r			Marc S	. Weii	ner, #32,181	
/cqc							·

PATENT

JC18 Rec'd PCT/PTO 0 2 MAY 2001

IN THE U.S. PATENT AND TRADEMARK OFFICE

Applicant:

AHO, Yrjo et al.

Conf.:

Int'l. Appl. No.:

PCT/FI99/00910

Appl. No.:

New

Group:

Filed:

May 2, 2001

Examiner:

For:

COATED PAPERBOARD, PROCESS FOR MANUFACTURING

THE SAME AND PRODUCTS OBTAINED THEREOF

PRELIMINARY AMENDMENT

BOX PATENT APPLICATION

Assistant Commissioner for Patents Washington, DC 20231

May 2, 2001

Sir:

The following Preliminary Amendments and Remarks are respectfully submitted in connection with the above-identified application.

AMENDMENTS

IN THE SPECIFICATION:

Please amend the specification as follows:

Before line 1, insert --This application is the national phase under 35 U.S.C. § 371 of PCT International Application No. PCT/FI99/00910 which has an International filing date of November 1, 1999, which designated the United States of America and was published in English.--

IN THE CLAIMS:

Please amend the claims as follows:

- 9. (Amended) Paperboard according to claim 5, characterized in that the total weight of the coating (3) is at most $25g/m^2$, preferably $13-22g/m^2$.
- 10. (Amended) Paperboard according to claim 1, characterized in that the fibre material layers comprise a three-layer structure (2), in which the middlemost layer is a thicker layer (4) consisting of a mixture of chemical pulp and CTMP, the thinner layers (5) on both sides of it consisting substantially of pure chemical pulp.
- 11. (Amended) A method for manufacturing a coated paperboard (1) according to claim 1, characterized in that the polymer forming the outer layer (6) of the coating and the polymeric mixture forming the inner layer (7) are coextruded together onto a moving paperboard web.
- 12. (Amended) The use of the coated paperboard (1) according to claim 1 as a heat-resistant oven board.
- 14. (Amended) The use of the coated paperboard (1) according to claim 1 as a liquid packaging board.

15. (Amended) An oven dish (8), characterized in that it has been manufactured of the paperboard (1) according to claim 1 so that the polymeric coating of the paperboard is attached to the interior surface of the dish (8).

REMARKS

The specification has been amended to provide a cross-reference to the previously filed International Application. The claims have also been amended solely to delete improper multiple dependencies so as to place the application into better form for examination. Entry of the present amendment and favorable action on the above-identified application are earnestly solicited.

Attached hereto is a marked-up copy of the changes made to the application by this Amendment.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. § 1.16 or under 37 C.F.R. § 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

Marc S. Weiner, #32,181

P.O. Box 747

Falls Church, VA 22040-0747

(703) 205-8000

Attachment: Version With Markings Showing Changes Made

MSW/cqc 0696-0178P

(Rev. 01/22/01)

VERSION WITH MARKINGS SHOWING CHANGES MADE

The specification has been amended to provide cross-referencing to the International Application.

The claims have been amended as follows:

- 9. (Amended) Paperboard according to [one of the claims 5-8, characterised] claim 5, characterized in that the total weight of the coating (3) is at most $25g/m^2$, preferably $13-22g/m^2$.
- 10. (Amended) Paperboard according to [one of the preceding claims, charactertised] claim 1, characterized in that the fibre layers comprise a three-layer structure (2), in which the middlemost layer is a thicker layer (4) consisting of a mixture of chemical pulp and CTMP, the thinner layers (5) on both sides of it consisting substantially of pure chemical pulp.
- 11. (Amended) A method for manufacturing a coated paperboard (1) according to [one of the preceding claims, characterised] claim 1, characterized in that the polymer forming the outer layer (6) of the coating and the polymeric mixture forming the inner layer 97) are coextruded together onto a moving paperboard web.
- 12. (Amended) The use of the coated paperboard (1) according to [one of claims 1-10] claim 1 as a heat-resistant oven board.

- 14. (Amended) The use of the coated paperboard (1) according to [one of claims 1-10] claim 1 as a liquid packaging board.
- 15. (Amended) An oven dish (8), [characterised] characterized in that it has been manufactured of the paperboard (1) according to [one of claims 1-10] claim 1 so that the polymeric coating of the paperboard is attached to the interior surface of the dish (8).

VPRTS

5

10

1

Coated paperboard, process for manufacturing the same and products obtained thereof

The object of the present invention is a coated paperboard for food, comprising one or more layers of fibre material and a heat-resistant polymeric coating, which gets into contact with food. Further, the invention relates to the manufacturing process and use of such a paperboard, and to a number of products obtained thereof.

A heat-resistant oven board is used as material for such food dishes and packages, which have to withstand heating in a common or microwave oven. A typical heatable food dish is an oven dish, which may be used as part of a finished package for heatable food, but which may also be marketed to consumers as a separate product. The polymeric coating of an oven board makes the paperboard water and grease resistant, and the polymer has to withstand the temperatures used in heating, typically at least 230 °C.

15 It has been known to use polypropylene or polyesters, such as polyethylene terephthalate (PET) as coating for oven boards. The problem with some of these known polymers has been insufficient heat resistance. Another problem relating to all polyesters used as coatings is the poor adhesion of the polymer to the paperboard. In order to achieve sufficient adhesion, the coating has to be spread onto the paperboard in layer thicknesses which are at least approx. 35 – 40 g/m². If the layer is thinner, there is a danger of it coming off, for example, due to vapour released from the paperboard. The use of possible binding agents improving the adhesion has been restricted by their poor heat resistance. Pin holes are also easily left in a thin polymeric layer.

Polyesters as such, and especially PET with a high melting point, are very well adapted to be used as coatings for oven paperboard. These polymers are compatible with food, because of their sufficient mechanical strength and heat resistance, and because their organoleptic advantageousness is kept at oven temperatures, they are heat-sealable and they may be spread onto the paperboard by extrusion. The only problem is caused by layer thicknesses which indicate a high material consumption and high amounts of polymer contained in the waste taken to dumping areas or material recycling. The need for reduction in polymer consumption is especially emphasised as even stronger and thinner fibre bases for paperboard have been developed and as the norms concerning waste take into account also the relative

amount of polymer compared with fibre material included, besides the absolute amount.

The object of the present invention is to form a coated paperboard, in which the adhesion of the polymeric coating to the paperboard has been improved, while simultaneously making the coating thinner and less prone to hole formation as before. It is characteristic of the paperboard of the invention that it is formed of superimposed polymeric layers, comprising an outer layer in which the melting point for the polymer used is at least 230 °C, and an inner layer placed against the fibre material layer, the inner layer including polymer with a melting point of at least 230 °C blended with another polymer achieving adhesion between the coating and fibre material, the melting point of this polymer being 130 - 185 °C.

5

10

15

20

25

The outer layer of the two-layer polymeric coating of the paperboard of the invention contacting the food thus comprises a heat-resistant polymer with the necessary oven properties and preferably consisting of some known coating polymer for oven boards that has been tested in use. According to the invention, adhesion of the outer polymeric layer to the paperboard, i.e. to the fibre material layer below, is achieved by an inner adhesion layer in which another adhesive polymer with a lower melting point has been blended with the heat-resistant polymer. Because of the heat-resistant polymer melting at or above 230 °C, the inner layer withstands heating in a stove or microwave oven at the same time as it is modified by said polymer melting at lower temperatures so that its adhesion to the fibre material is substantially better than before. Due to improved adhesion, the two-layer polymeric coating for the paperboard of the invention may be produced with a considerably smaller amount of polymer, even when added together, than the previous one-layer coatings for oven paperboards.

Besides oven boards, the paperboard of the invention is also applicable to liquid packaging boards, e.g. drinking cups and other disposable dishes, due to its compatibility with food and its heat-sealability.

The mixture ratio of polymers in the inner coating layer of the paperboard of the invention preferably is within the range of 85 − 97% of polymer with a higher melting point (≥ 230 °C) and 3 − 15% of adhesive polymer with a lower melting point (130 - 185 °C). The polymer with the higher melting point is most preferably the same polymer as has been used in the outer layer of the coating.

A preferable polymer to be used in the outer coating layer and also as the second polymeric component of the inner coating layer is polyethylene terephthalate, such as Eastapak PET copolyester with a melting point of 240 °C, manufactured by Eastman Chemical Company, or Eastapak PET polyester 12440, manufactured by the same company. In PET-based copolyesters, comonomers used in relatively small amounts (approx. 1 – 10%) may comprise, for example, cyclohexane dimethanol (CHDM) or isophthalic acid (IPA), which improve the processability of the polymer. Other polymers may comprise polybutene terephthalate, polyethylene glycol-modified polyethylene terephthalate (PETG), polyethylene naphthalene (PEN), and polypenthene, which, used as such, all adhere poorly to fibre material; but the problem of adhesion related with these may be solved with a two-layer coating of the present invention.

5

10

15

20

25

30

The adhesive polymeric component melting at 130 - 185 °C for the inner coating layer may preferably comprise a terephthalate-based copolyester which especially well both blends with and binds to said polyethylene terephthalate melting at or above 230 °C. An example of such polymers is Eastobond copolyester 19411 manufactured by Eastman Chemical Company, in which the used comonomer is diethylene glycol (DEG), reducing the crystallinity of the polymer and increasing the polarity due to its OH groups, these factors improving the adhesion between the polymer and the paperboard.

The invention is further applicable in an advantageous way so that, besides the two polymeric components, the inner coating layer is provided with fine mineral substance. It has been noted that mineral substance facilitates the coextrusion of polymeric layers onto paperboard and makes it possible for the polymeric layer to be even thinner than before. An especially suitable mineral is, for example, calcium carbonate but, for example, also titanium oxide or talcum are usable. When using a mineral component, the composition of the inner coating layer may preferably vary within the range of 80 - 90% of polymeric component melting at a higher temperature (≥ 230 °C), 3 - 10% of adhesive polymeric component melting at a lower temperature (130 - 185 °C), and 5 - 15% of mineral substance.

The total weight of a two-layer polymeric coating of the paperboard of the invention is preferably at most 25 g/m², most preferably 15 - 22 g/m². By using said mineral substance as part of the inner layer, the total weight of the coating may be in an even lower range, i.e. 13 - 22 g/m².

The fibre base for the paperboard of the invention preferably consists of a three-layer paperboard, in which the middlemost layer is a thicker layer of a mixture of chemical pulp and CTMP, and the layers on both sides of this layer substantially consist of pure chemical pulp. The polymeric coating may be spread either on only one side or both sides of the paperboard.

5

10

15

20

It is characteristic of the method for manufacturing a coated paperboard of the invention that the polymer forming the outer layer of the coating and the polymeric mixture forming the inner layer are together coextruded onto a moving paperboard web. Extrusion is followed by rapid cooling during which the polymer remains in an amorphic state so that it is heat-sealable. Most preferable for coextrusion is a layer combination in which the outer layer to be placed onto the paperboard consists of polyethylene terephthalate, such as said PET polyester 12440 or PET copolyester 9921, the inner layer comprising a mixture of polyethylene terephthalate, such as either of the said products, of a terephthalate-based copolyester, such as the said Eastman copolyester 19411, and of calcium carbonate. However, in the applications of the process, the layers to be coextruded may vary, as is apparent of the above description of the paperboard of the invention.

Products to be manufactured of the paperboard of the invention comprise, above all, paperboard oven dishes for heating food in a common or microwave oven. For protecting the paperboard base of the dish and for preventing the food from sticking to the dish, the polymeric coating of the paperboard has to be provided at least to the interior surface of the dish. However, it is preferable to provide both the interior and exterior surface of the dish with a polymeric coating, in which case the paperboard is also protected from possible spatters and grease in the baking plate.

The oven dish of the invention may be formed of paperboard coated with polymer either by pressing or, alternatively, by folding and joint sealing the folds thus produced to the exterior surface of the dish. In either case, the polymeric coating withstands the joint sealing and other moulding measures without hole formation or breaking.

According to the invention, the oven dish may form part of a finished package for food, the package and its contents being heatable as such in a stove or microwave oven. Besides the dish and the heatable food packed into it, such a package comprises a separate protective cover or wrapping, which is removed before heating, when necessary.

As mentioned above, the paperboard of the invention is also usable in products manufactured of liquid packaging board, such as disposable cups, plates and packages. Here the advantage of polyesters, such as PET, is that they are heat-sealable and that they do not give any taste or smell to foods in contact with them. With the invention, it has been possible to improve the mutual adhesion of PET and paperboard and to reduce the thickness of the PET layer.

The invention further comprises the use of the coated paperboard described above as oven board or as liquid packaging board and, especially, the use of it as part of a consumer package shaped as a dish, containing heatable food.

10

20

25

30

5

The invention is next described in more detail with the help of examples, referring first to the enclosed drawings, in which

Fig. 1 is a schematic view of a polymer-coated paperboard of the invention;

Fig. 2 is a schematic view of a second paperboard of the invention;

15 Fig. 3 shows an oven dish manufactured of paperboard of Fig. 2; and

Fig. 4 shows on enlarged scale a section of the wall structure of a dish in accordance with Fig. 3 at the edge of the dish.

In Figure 1, there is shown the layer structure of paperboard 1, the other side of which is provided with a polymeric coating. The fibre layers of the paperboard are together referred to with the reference number 2 and the polymeric coating with the reference number 3 in the figure.

The fibre layers 2 consist of a three-layer paperboard, the thicker middle layer 4 of which is a mixture of sulphate pulp and CTMP, the outer layers 5 on the both sides of the middle layer consisting of sulphate pulp. The share of the middle layer 4 of the weight of the fibre layers 2 is approx. 60%, and the share of both the said sulphate pulp layers 5 is approx. 20%. The total weight of the fibre layers 2 without the coating layers may be approx. 200 – 400 g/m², for example, approx. 225 g/m². When necessary, filler (not shown) may be used on the surfaces of the three-layer paperboard. In Figure 1, the polymeric coating 3 consists of an outer layer 6, in which a polymer compatible with food has been used, the melting point of which is at least 230 °C, and of an inner layer 7 coextruded with the outer layer, the inner layer comprising a polymer, the melting point of which is at least 230 °C, blended

with another adhesive polymer with a melting point of 130 - 185 °C. Besides the said polymeric components, the inner layer 7 may contain a fine mineral substance, such as calcium carbonate. The polymeric coating 3 may consist of an outer layer 6 of, for example, polyethylene terephthalate with a melting point of 240 °C, and of an inner layer 7, which includes a mixture of 80 - 90% of the same polyethylene terephthalate as in the outer layer, 3 - 10% of adhesive terephthalate-based copolyester with a melting point of 159 °C, and 5 - 15% calcium carbonate. The added weight of the layers 6, 7 of the polymeric coating 3 then is preferably 13 - 20 g/m².

The coated paperboard of Fig. 2 is structurally similar to that shown in Fig. 1, with the exception that its both sides are provided with polymeric coating 3. The fibre layers 2 are thus formed of a similar three-layer paperboard as in the application in Fig. 1, and also the materials and weight of the polymeric coatings 3 on both sides of the paperboard 1 may correspond to those shown in Fig. 1. The paperboard of both Fig. 1 and Fig. 2 is suitable to be used as material for oven dishes; in this case, the paperboard of Fig. 1 has the advantage that the amount of polymer in relation to fibre material is smaller, and the advantage of the application in Fig. 2 is that the paperboard is better protected from moisture and grease.

In Figure 3, there is shown an oven dish manufactured of the paperboard of Fig. 2, which, for example, is suitable for a package for ready-prepared foods. The dish 8 thus comprises a polymeric coating 3 both on its interior and exterior surface, as is shown in Fig. 4.

Examples

5

20

Example 1

One side of a three-layer paperboard with a weight of 295 g/m² and propagation speed of 300 m/min, was provided by coextrusion with a top layer of Eastapak PET copolyester 9921 and with an inner layer comprising a mixture of 80 weight % of Eastapak PET copolyester 9921, 10 weight % of adhesive Eastobond copolyester 19411, and 10 weight % of calcium carbonate. The extrusion temperature was 290 °C and the air gap, i.e. the distance of extrusion nozzles from the paperboard web, was 18 cm. The weight of both the extruded polymeric layers was 11g/m², i.e. the total weight of the two-layer coating thus obtained was 22 g/m².

Examples 2-4

The procedure of Example 1 was followed with the exception that the weights of the layers extruded in weight ratio 1:1 were 10 g/m², 9 g/m² and 8 g/m², and, respectively, the total weights of the two-layer coating were 20 g/m², 18 g/m² and 16 g/m².

Example 5

5

10

15

30

A two-layer coating was coextruded on both sides of a three-layer paperboard with a weight of 295 g/m² and propagation speed of 300 m/min, the top layer of the coating comprising Eastapak PET copolyester 9921 and the inner layer being a mixture of 80 weight % of Eastapak PET copolyester 9921, 10 weight % of adhesive Eastobond copolyester 19411, and 10 weight % of calcium carbonate. The extrusion temperature was 290 °C and the air gap, i.e. the distance of extrusion nozzles from the paperboard web, was 18 cm. The weight of each of the extruded polymeric layers was 11 g/m² so that a two-layer coating with a total weight of 22 g/m² was produced on both sides of the paperboard.

Example 6

The procedure of Example 5 was followed with the exception that the weight of each of the extruded polymeric layers was 10 g/m^2 so that a two-layer coating with the total weight of 20 g/m^2 was produced on both sides of the paperboard.

20 Reference material

One side of a three-layer paperboard with a weight of 295 g/m² and propagation speed of 300 m/min was extruded with Eastapak PET copolyester 9921 to produce a one-layer coating. The extrusion temperature was 290 °C and the air gap in extrusion was 18 cm. The weight of the extruded layer was 22 g/m².

25 Tearing tests

The adhesion of the coating was evaluated from the coated paperboards produced in accordance with Examples 1-4 and the reference material by tearing off the polymeric coating from dry paperboard. The evaluation took place on a scale of 1-6, in which the best value 1 represented a 100% fibre tear, the surface of the polymeric coating torn off the paperboard then being totally covered by fibres, the poorest value 6 representing missing adhesion, in which case the surface of the coating torn off from the paperboard was clear, without adhered fibres. The value 6

indicates a rejected result, while the value 5 again is still sufficient to keep the coating adhered to the paperboard as the paperboard is being processed into a food dish.

Further, wet adhesion was evaluated from the same materials by soaking the paperboard samples in room-temperature water and by tearing off the polymeric coating from the completely waterlogged paperboard. The scale was 1-3, the values 1 and 2 representing an approved and the value 3 a rejected result.

The test results have been shown in the following Table I.

Table I

20

25

10	Material	Dry adhesion	Wet adhesion
	Example 1	1	1
	Example 2	1	1 ,
	Example 3	3	2
	Example 4	4	2
15	Reference material	6	3

Processing into an oven dish and heating tests

Oven dishes were manufactured of paperboards with polymeric coatings in accordance with Examples 1 – 4 by stamping a paperboard with a moisture rate of 11% by a hydraulic compression tool, the temperature of which was 200 °C. The dishes thus obtained were then kept in an oven with a temperature of 230 °C for 30 minutes.

In stamping, the paperboard is placed into a high temperature for a short time, the moisture contained in the paperboard evaporating and generating a pressure which may remove some of the coating. Also in an oven there is the danger of gas bubbles forming beneath the coating and the coating unsticking. In the tests carried out, the paperboards in accordance with Examples 1-4, however, withstood the stamping and heating in an oven without any signs of the coating unsticking or of some other damages.

Heat sealing tests

5

10

Drinking cups were manufactured of paperboards coated on both sides with polymer according to Examples 5 and 6 by heat sealing at a sealing temperature of 250 °C. Risk factors in the joint sealing are that the joints remain leaking or that pin holes will exist in the area of joints in the coating layer, due to heating.

Sealability was evaluated by filling the cups with a test liquid containing approx. 50% of water, approx. 50% of ethanol and a small amount of colouring agent, the penetration of which into the paperboard is an easily observable sign of failed sealing. In the test, no leaks were observed in the joints of neither cup manufactured of the cardboard of the example.

It is obvious for one skilled in the art that the applications of the invention are not limited to the above examples, but they may vary within the scope of the following patent claims.

Patent claims

20

25

- A coated food paperboard (1), comprising one or several fibre material layers (2, 4, 5), and a heat-resistant polymeric coating (3) getting into contact with food, said coating (3) consisting of superimposed polymeric layers comprising an outer layer (6), the melting point of the polymer of which is at least 230 °C, and an inner layer (7) placed against the fibre material layer (5), to achieve adhesion between the coating and the fibre material, characterized in that the inner layer (7) comprises a first polymer with a melting point of at least 230 °C, blended with a second polymer which is an adhesive polymer with a melting point of 130 185 °C in a ratio of 85 97% of said first polymer and 3 15% of said second polymer.
 - 2. Paperboard according to claim 1, characterised in that the polymer of the outer layer (6) and the one of the polymers of the inner layer (7) are of the same polymeric material.
- 3. Paperboard according to claim 2, **characterised** in that the outer layer (6) of the coating is polyethylene terephthalate, and the inner layer (7) is a mixture of polyethylene terephthalate and a terephthalate-based copolyester with a lower melting point.
 - 4. Paperboard according to some of the preceding claims, characterised in that the total weight of the polymeric coating (3) is at most 25 g/m², preferably 15 22 g/m².
 - 5. Paperboard according to claim 1, **characterised** in that the inner layer (7) of the coating further has blended in it fine mineral substance.
 - 6. Paperboard according to claim 1, characterised in that the inner layer (7) comprises 80 90% of polymer with a melting point of at least 230 °C, 3 10% of polymer with a melting point of 130 185 °C, and 5 15% of mineral substance.
 - 7. Paperboard according to claim 5 or 6, characterised in that the mineral substance is calcium carbonate.
- 8. Paperboard according to claim 7, **characterised** in that the outer layer (6) of the coating is polyethylene terephthalate and the inner layer (7) is a mixture of polyethylene terephthalate, a terephthalate-based copolymer with a lower melting point, and calcium carbonate.

- MAT 30 PARIOT Paperboard according to one of the claims 5 - 8, characterised in that the total weight of the coating (3) is at most 25 g/m², preferably 13 - 22 g/m².
 - Paperboard according to one of the preceding claims, characterised in that the fibre material layers comprise a three-layer structure (2), in which the middlemost layer is a thicker layer (4) consisting of a mixture of chemical pulp and CTMP, the thinner layers (5) on both sides of it consisting substantially of pure chemical pulp.
 - 11. A method for manufacturing a coated paperboard (1) according to one of the preceding claims, characterised in that the polymer forming the outer layer (6) of the coating and the polymeric mixture forming the inner layer (7) are coextruded together onto a moving paperboard web.

10


- The use of the coated paperboard (1) according to one of the claims 1-10 as a heat-resistant oven board..
- The use of the paperboard according to claim 12 as part of a consumer package shaped as a dish (8) for heatable food.
- The use of the coated paperboard (1) according to one of the claims 1-10 as a 15 liquid packaging board.
 - An oven dish (8), characterised in that it has been manufactured of the paperboard (1) according to one of the claims 1-10 so that the polymeric coating of the paperboard is attached to the interior surface of the dish (8).
- An oven dish according to claim 15, characterised in that it has been 20 manufactured of paperboard (1) by compression.
 - An oven dish according to claim 15, characterised in that it has been manufactured of paperboard (1) by folding and joint sealing the folds thus produced to the exterior surface of the dish.
- A heatable food package, characterised in that it comprises the oven dish (8) 25 according to one of the claims 15 - 17, food intended to be heated in the dish, and a removable protective cover or wrapping closing the dish.

(57) Abstract

The invention relates to a coated food paperboard (1), to the manufacturing process and use of the same, and to products obtained thereof. The paperboard (1) comprises one or several fibre material layers (2), such as a three-layer structure consisting of a middle layer (4) of a mixture of sulphate pulp and CTMP and of sulphate pulp layers (5) on both sides of it, and of a polymeric coating (3) getting into contact with food, either on one side or on both sides of the paperboard. According to the invention, the coating (3) consists of an outer layer (6), the melting point of the polymer used in which is at least 230 °C, and of an inner layer (7) placed against the fibre material layer (5); in this inner layer, a polymer with a melting point of at least 230 °C is blended with another adhesive polymer, the melting point of which is 130 - 185 °C. Further, the inner layer (7) may be provided with mineral substance, such as calcium carbonate. In accordance with the invention, the paperboard (1) is manufactured by coextrusion of superimposed polymeric layers (6, 7). The paperboard (1) of the invention is suitable for liquid packaging or oven board, and products manufactured of the paperboard comprise especially oven dishes and consumer packages for food, which include the dish and which may be heated as such.



1/1






Fig 2.




Fig 4.

FEB-21-2003 FRI 03:50 PM BSKB MISTA-BERGGREN OY AB 05-10-2001 14:11

FAX NO. 703 205 8050

P. 06

+358-9-6833944

" 14Q \$.002/009 T-100




0696-0178P Attorney Docket No. BIRCH, STEWART, KOLASCH & BIRCH, LLP

PLEASENOTE: YOUMUST COMPLETETHE FOLLOWING P.O. Box 747 7-Palls Church, Virginia 22040-0747 Telephone, (703) 205-8000 (1 Facsimile: (703) 205-8050

COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT AND DESIGN APPLICATIONS

As a below named inventor, I hereby declare that my residence, post office address and diszenship are as stated next to my name;

lasert Fida	invention worklast	rentors are named below) of	mic anolece muret M	one inventor is named below hich is claimed and for what accuring the s	wen a patent t	s sought on the
Fill in Appropriate Information - For Use Without	the specification of what the specification United States Ap	nich is attached hereto. If not was filed on 2 May 29 plication Number 09/83	itteched hereto, Ob 201	tained thereof		as
Specification Amsched:	and amended on the specification	T				as PCT
	amended under	C. F. Article 19 on				; and was pplicable)
	I acknowledge the Regulations, \$1.56. I do not know and thereof, or patented of	at I have reviewed and under diment referred to above, and the same was a described in any printed prication, that the same was not, that the invention has not as in any country foreign this more than twelve months reficate on this invention has y legal representatives or assign priority benefits under ilisted below and have also defined of the application on which to the different princate on any legal representatives or assign priority benefits under ilisted below and have also defined the application on which the application on which the different priority benefits under the application on which the application on which the different priority benefits under the application on which the application on which the different priority benefits under the application on which the application on which the different priority benefits under the application on which the different priority the application on which the different priority that the application on which the different priority that the different priority the different priority that the different pr	on which is material ever known or used it blication in any count	to patentability as defined to the United States of American before my or our invent	in Title 37, C	ode of Federal
t a selle to a	Prior Foreign Applic		Monty is daimed:		Priority (
Insert Priority Information	982372	Finland		ember 2, 1998	እስ. እ	
(й аррторичы)	(Number)	(Country)	(Month)	Day/Year Filed)	Yes	No ··
	(Number)	(Country)	(Month/	Day/Year Filed)	Yes □	No
	(Number)	(Country)	(Month/	Day/Year Filed)	∏ Yes	□ No
	(Number)	(Country)		Day/Year Filed)	Yes	720
lusare Provisional Application(s); (if any)	(Application Number)	t under Title 35, United State		Julied Sintes provisional ap g Date)	ptications(s) lis	ted below,—
	(Application Number)		(Filing	g Date)		
	All Foreign Applications the Filing Date of This A	, if any, for any Patent or Inv oplication:	entor's Cartificate Files	i More than 12 Months (6 M	lonths for Desi	gns) Prior to
nsecz Raquestod Normations	Country	Application N	umber	Date of Filing (Month/I	Day/Year)	
4 аррторгізіс)	I hereby claim the benefit insofer as the subject me application in the maned internation which is man internation which is maned between the filling date of	under Title 35, United States ther of such of the claims o provided by the first paragr erial to the patentability as de the prior application and the	Code, \$120 of any Uni f this application is of ph of Title 35, United tined in Title 37, Code national or PCT interna-	ted States and/or PCT appli tot disclosed in the prior I States Code, \$12, I acknow of Federal Regulations, \$1.3 ational filing date of this app	cation(s) listed Inited States a viedge the duty 36 which becan plication.	below and, nd/or PCT to disclose he available
witt Frier U.S.	(Application Number)	(Filing Date)		(Status - patented, pendi		



FAX NO. 703 205 8050

P. 07

+358-9-6933944

Afterney Docket No.

I hereby appoint the following attorners to prosecute this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application pagers to the attorneys with a below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary.

Raymond C. Stewart Joseph A. Kolasch Bernard L. Sweensy Charles Gorenstein Leonard R. Svensson Andrew D. Meikle Joe McKlinney Muncy John W. Bailey Gary D. Yacura	(Reg. No. 21,066) (Reg. No. 22,463) (Reg. No. 21,448) (Reg. No. 29,271) (Reg. No. 30,330) (Reg. No. 32,334) (Reg. No. 32,334) (Reg. No. 32,381) (Reg. No. 32,416)	Terroll C. Birch James M. Siattery Michael K. Muster Gerald M. Murphy, Jr. Terry L. Clark Marc S. Weiner Donald J. Daley John A. Castellano	(Reg. No. 19,382) (Reg. No. 29,380) (Reg. No. 29,690) (Reg. No. 28,977) (Reg. No. 32,544) (Reg. No. 32,544) (Reg. No. 34,313) (Reg. No. 33,094)
---	---	---	--

Send Correspondence to:

BIRCH, STEWART, KOLASCH&BIRCH, LLP

P.O. Box 747 Falls Church, Virginia 23040-0747 Telephone: (703) 203-8000 I Facsimile: (703) 205-8050

CustomerNo.2292 or

PLEASENOTE: -DLETE THE FOLLOWING:

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful bits statements and the like so made are purishable by fine or imprisonment or both under Section 1001 of Title 18 of the United States Code and that willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name or Plant	y at the application or any	going restred their	₽or_
Full Name of Plant are fully Indeed to some its Indeed The Indeed	CIVEN NAME/FAMILY NAME INVENTOR'S SIGNATURE YE jo AHO		DATE 27.02.01
Intert Consensity —	Residence (City, State & Country) Rauha, Finland	CITIZENSH	T.F
Insure Post Office Address 44	MAILING ADDRESS (Complete Short)	Finnis	h
Fall Name of Superior Internation is any	Karhunpääncie 99, FIN-55300 Rauha, Finla GIVEN NAME/FAMILY NAME INVENTORSSIC, 11/22	πd	
2.00	Residence City Sport Course		! DATE" 1/2,06.01
<i>~</i>	MAKING ADDRESS: Campion Street A Li	Finnish	P
No ut Thuu	Chroming Fin-49210 Huutjärvi, Finla	and	
2.00	Risto SALMINEN Residence (City, State & Country)		DATE 12.06 2001
	Karhula, Finland	Finnish	2007
L	MAILNG ADDRESS (Complete Street Address including City, State in Country) Rauduskacu 9, FIN-48600 Karhula, Finland	······································	
Profits of Function reasonable of Assay 1925 Above to	CIVEN NAME/FAMILY NAME : INVENTORS SIGNATURE		DATE*
	Residence (City, State & Country)	CHIZENSHIP	
7	CAILING ADDRESS (Complete Smeet Address including City, State to Course)		
(4 9 2 (W 27 baar)	DATE OF SIGNATURE		

Received from < 703 205 8050 > at 2/21/03 3:58:09 PM [Eastern Standard Time]-

P. 09

FAX NO. 703 205 8050

FEB-21-2003 FRI 03:51 PM BSKB

+359-9-5233844

-140 \$.005/009 T-100

Attorney Docket No.

I hereby appoint the following attorneys to prospect this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application papers to the attorneys identified below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary.

Raymond C. Stewart	(Reg. No. 21,066)	Tecreli C. Birch	(Reg. No. 19,382)
Joseph A. Kolasch	(Reg. No. 22,463)	James M. Slattery	(Reg. No. 28,380)
Bernard L. Sweeney	(Reg. No. 24,448)	Michael K. Mutter	(Reg. No. 29,680)
Charles Gorenstein	(Reg. No. 29,271)	Gerald M. Murphy, Jr.	(Reg. No. 28,977)
Leonard R. Svensson	(Reg. No. 30,330)	Terry L. Clark	(Reg. No. 32,644)
Andrew D. Meikle	(Reg. No. 32,868)	Marc S. Weiner	(Reg. No. 32,181)
Joe McKinney Muncy	(Reg. No. 32,334)	Donald J. Daley	(Reg. No. 31,313)
John W. Bailey	(Reg. No. 32,861)	John A. Castellano	(Reg. No. 35,094)
Gary D. Yacura	(Reg. No. 35,416)	-	

Send Correspondence to:

BIRCH, STEWART, KOLASCH&BIRCH, LLP

or CustomerNo.2292

P.O. Box 747 _ Falls Church, Virginia 22040-0747 Telephone: (703) 205-8000 _ Facsimile: (703) 205-8050

PLEASENOTE:
YOUMUST
COMPLETE
THE
FOILOWING:

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Numer of First or Self to reports factor hams of the This Inject the This Document is Signed	Given name/family name	INVENTOR'S SIGNATURE		DATE*	
Treats Residence Institution of	Residence (City, State & Country)		CITIZENSHIP		
Ireans Possi Othles Addresse sh	MAILING ADDRESS (Complete Street Address t	ncluding City, State & Country)			
Figh Status of Encional Inventors of English was above	CIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE		DATE*	
	Residence (City, State & Country)		CITIZENSHIP		
·	MAILING ADDRESS (Complete Street Address to	ncluding City, State & Country)			
Full Hamp of Third Inverser, ii any: are aborty	GIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE		DATE*	
	Residence (City, State & Country)		CITIZENSHIP		
	MAILING ADDRESS (Complete Street Address in	icluding City, State & Country)			
Full Hame of Fourth Investor, it and for allows	GIVEN NAME/FAMILY NAME Bruce FOSTER	INVESTORS SIGNATURE	72	DATE* 115ep 01	
H. J.	Longvious, Toxas, USAA. Oxford, Connecticut, USA U.S.				
	MAILING ADDRESS (Complete Street Address in 617, Ruth Lynn Drive, Lot		U 5 A.		
Page 2 of 3 (3 on, 10/27/2000)	DATEOFSIGNATURE 87 THO	rson Road, Oxfo	rd, CT	06478	